

INVENGO XC-AB700 UHF, HF RFID READER



About Invengo's XC-AB700 Hand Held Reader

Invengo's XC-AB700 is a compact, rugged and excellent performing RAIN RFID (UHF), HF hand held reader. With a powerful processor, Windows Mobile embedded, generous base memory and multiple connectivity and data capture options, it is suitable for supply chain, asset, livestock and industrial tracking applications.



Invengo – the global RFID technology provider – is a leading developer and manufacturer of high quality, intelligent RAIN RFID and HF/NFC connectivity solutions and consumables (tags & inlays) utilized in the Internet of Things. With a focus on RFID innovation, Invengo has created a leading product line in retail, (industrial) laundry, library, (public) transportation, healthcare, and many other industries.

Invengo Technology Pte. Ltd. (SG) is the International Headquarters of Invengo Information Technology Co. Ltd, listed on Shenzhen Stock Exchange (SZSE: 002161.SZ). Employing over 600 people globally, Invengo is one of the largest publicly traded, RFID / IoT oriented companies in the world.

Features

- Windows Mobile Embedded 6.5
- Marvell PXA 320 806MHz Processor
- 256MB RAM/512MB ROM
- UHF Gen 2 RFID 865~868 MHz and 902~928 MHz
- 2D Imager
- WLAN
- Bluetooth

All features and specifications described are subject to change without notice.

Product Specifications

Performance

Processor	Marvell™ PXA 320 806MHz
Operating System	Windows CE 5.0 Windows Embedded handheld 6.5
Memory	256MB (512MB) RAM 512MB (1GB) ROM
Display	3.5" QVGA with Backlight, TFT LCD, 240x320 px, 262, 144 Color (VGA)
Weight	0,29kg/0.64 Lbs (PDA only)
Operating Temp.	-20°C to 60°C (-4°F to 140°F)
Storage Temp.	-30°C to 70°C (-22°F to 158°F)
Humidity	95% non-condensing
Drop Spec.	1.5M Drop to concrete
Dust & Water Proof	IP65

Physical

Audio	Phone Receiver, Speaker, Ear Jack,
Standard I/O Port	Microphone USB 1.1 Client/USB Host & Serial
Expansion Slot	(RS-232) via gender cable or Cradle 1 Micro SD Slot (SDHC), 1 SIM Slot, 1 SAM Slot
Notification	Vibrator and LED, Speaker
Dimensions (L x W x H)	172 x 88 x 33 (38) mm 6.77 x 3.46 x 1.30 (1.50) in

Battery Supply

Main Battery	Lithium-Ion Polymer 3.7V 2,960mAh (Rechargeable) Up to 4,400mAh
Backup Battery	Lithium-Ion Polymer 3.7V 80mAh (Rechargeable)
Power Adapter	Input AC 110V to 240V Output DC 5V 3A

Network Characteristics

WLAN	IEEE 802.11 b/g/a Compliant
Bluetooth	Class II, v2.1 + EDR
Radio	MODEM 3G (GSM / GPRS / HSDPA / HSPA+)
GPS	Internal Antenna

Data Capture Device

Barcode Engine	1D Laser or 2D Imager Scanner
Camera	3.0 Mega Pixel Auto Focus, Flash

UHF Reader/Writer

Frequency	860 to 960 MHz
Reading range	0 to 7 m/ 0 to 23 Feet
Writing range	0 to 3 m/ 0 to 10 Feet
RF output	1W EIRP
Protocol	GEN2, ISO/IEC 18000-63 and ISO/IEC 18000-62
Special function	Anti-Collision

HF Reader/Writer

Applied RFID Tag	ISO/IEC 15693, MIFARE, ISO/IEC 14443 A/B
Reading range	Based on Tag : 0-10 cm (Internal or External)

Cradle

Standard Interface	USB 1.1 Host / USB Client / DC Power Jack / Extra Battery Charger Serial (RS232) via gender cable
Ethernet Interface	RJ-45 Ethernet Interface

Accessories

Gun Handle Grip (Pistol Grip)	Body, UHF/HF Available
Gun Handle Battery	Lithium-Ion 3.7V 4,400mAh

APAC

Invengo Technology Pte. Ltd
10 Kallang Avenue
#05-15 Tower 2, Aperia
Singapore 339510

Office: +65 6702 3909
sales.apac@invengo.com

Americas

Invengo Technology Corp.
2700-160 Sumner Blvd.
Raleigh, NC 27616
United States of America

Office: +1 919 890 0202
sales.americas@invengo.com

EMEA

Invengo Technologies
180 Voie Ariane – Athéna 1
13600 La Ciotat
France

Office: +33 413 96 1111
sales.emea@invengo.com